

In the claims:

1. (Currently amended) A washer, comprising a body having an axis and provided with a first bearing face surface located at one axial side and adapted to cooperate with a nut, a second bearing face surface located at an opposite axial side and adapted to cooperate with an object, at least one third turning resistant surface adapted to cooperate with a thread of thea bolt, said body having a radially inner part provided with said turning resistant surface, a radially outer part and at least one resistive point arranged so that when the nut is turned and turns the bolt said body of the washer stops the bolt from turning and thereby the nut creates a pull on the bolt which elongates the bolt in an axial direction and applies to said body of the washer and to said turning resistant surface an axial force which overcomes the at least one resistive point so that ~~a portion~~said radially outer part of said body does not move radially or axially, while said radially inner part of said body of the washer with said turning resistant surface cooperating with the thread of the bolt is allowed to be pulled axially when the bolt elongates.

2. (Currently amended) A washer as defined in claim 1, wherein said body ~~has two parts arranged so that one~~ radially outer part

prevents initially an axial displacement of the other ~~the~~ radially inner part which is engaged with the bolt, and thereafter said ~~one of said parts~~ radially outer part is broken at said at least one resistive point under the action of the axial force.

3. (Original) A washer as defined in claim 1, wherein said body is formed as a one-piece integral element, which subsequently is broken at said at least one resistive point under the action of the axial force.

4. (Currently am ended) A washer as defined in claim 1, wherein ~~said body has two parts with one of said parts having~~ has a deformable formation which forms said resistive point and is formed so as to prevent initially an axial displacement of ~~the~~ said radially inner part which is engaged with the bolt, and thereafter said formation is deformed under the action of the axial force to allow an axial displacement of ~~the~~ said radially inner part engaged with the bolt relative to the other ~~said radially outer part~~ of said body.

5. (Original) A washer as defined in claim 4, wherein said formation is formed as a radially outwardly extending skirt-shaped portion.

6. (Original) A washer as defined in claim 4, wherein said formation is formed as a radially outwardly extending knurl-shaped portion.

7. (Currently amended) ~~A washer as defined in claim 4~~ A washer, comprising a body having an axis and provided with a first bearing face surface located at one axial side and adapted to cooperate with a nut, a second bearing face surface located at an opposite axial side and adapted to cooperate with an object, at least one third turning resistant surface adapted to cooperate with a thread of the bolt, said body having at least one resistive point arranged so that when the nut is turned and turns the bolt said body of the washer stops the bolt from turning and thereby the nut creates a pull on the bolt which elongates the bolt in an axial direction and applies to said body of the washer an axial force which overcomes the at least one resistive point so that a portion of said body of the washer is allowed to be pulled axially when the bolt elongates, wherein said body has two parts which are press fit over one another so as to form said resistive point, so that an axial displacement of said parts relative to one another is initially prevented, and thereafter under the action of the axial force one of said parts is axially displaced relative to the other of said parts.

8. (Currently amended) A fastener for connecting two parts which constitute an object, comprising a bolt having a thread; a nut screwable on said bolt; and a washer to be applied between the nut and the object and including a body having an axis and provided with a first bearing face surface located at one axial side and adapted to cooperate with the nut, a second bearing face surface located at an opposite axial side and adapted to cooperate with the object, and at least one third turning resistant surface adapted to cooperate with the thread of said bolt, said body of said washer having a radially inner part provided with said turning resistant surface, radially outer part, and at least one resistive point arranged so that when the nut is turned and turns the bolt said body of the washer stops the bolt from turning and thereby the nut creates a pull on the bolt which elongates the bolt in an axial direction and applies to said body of the washer and to said turning resistant surface an axial force which overcomes the at least one resistive point so that ~~a portion~~said radially outer part of said body does not move radially or axially, while said radially inner part of said body of the washer with said turning resistant surface cooperating with the thread of the bolt is allowed to be pulled axially when the bolt elongates.

9. (Currently amended) A fastener as defined in claim 8, wherein ~~said body has two parts arranged so that one~~radially outer part

prevents initially an axial displacement of ~~the other~~said radially inner part which is engaged with the bolt, and thereafter ~~said one of said parts~~said radially inner part is broken at said at least one resistive point under the action of the axial force.

10. (Currently amended) A fastener as defined in claim 8, wherein said body is formed as a one-piece integral element which includes said parts, which subsequently is broken at said breaking point under the action of the axial force.

11. (Currently amended) A fastener as defined in claim 8, wherein ~~said body has two parts with one of said parts having~~has a deformable formation which forms said resistive point and is formed so as to prevent initially an axial displacement of ~~the~~said radially inner part which is engaged with the bolt, and thereafter said formation is deformed under the action of the axial force to allow an axial displacement of ~~the~~said radially inner part engaged with the bolt relative to ~~the other~~said radially outer part of said body.

12. (Original) A fastener as defined in claim 11, wherein said formation is formed as a radially outwardly extending skirt-shaped portion.

13. (Original) A fastener as defined in claim 11, wherein said formation is formed as a radially outwardly extending knurl-shaped portion.

14. (Currently amended) ~~A fastener as defined in claim 8~~ A fastener for connecting two parts which constitute an object, comprising a bolt having a thread; a nut screwable on said bolt; and a washer to be applied between the nut and the object and including a body having an axis and provided with a first bearing face surface located at one axial side and adapted to cooperate with the nut, a second bearing face surface located at an opposite axial side and adapted to cooperate with the object, and at least one third turning resistant surface adapted to cooperate with the thread of said bolt, said body of said washer having at least one resistive point arranged so that when the nut is turned and turns the bolt said body of the washer stops the bolt from turning and thereby the nut creates a pull on the bolt which elongates the bolt in an axial direction and applies to said body of the washer an axial force which overcomes the at least one resistive point so that a portion of said body of the washer is allowed to be pulled axially when the bolt elongates, wherein said body has two parts which are press fit over one another so as to form said resistive point so that an axial displacement of said parts relative to one another is initially prevented, and thereafter

under the action of the axial force one of said parts is axially displaced relative to the other of said parts.

Claims 15-16 cancelled.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.